



TE Internal #: K1060709  
General Purpose Power Relay, DC, Monostable, 1 Form X SPST-NO-DM, 120 A Contact Rating, 16 VDC / 9 VDC Coil Voltage, KISSLING Series 29

Relay & Contactor Type: **General Purpose Power Relay**  
Current Type: **DC**  
Coil Magnetic System: **Monostable**  
Contact Arrangement: **1 Form X SPST-NO-DM**  
Contact Current Rating: **120 A**

Features

Product Type Features

Relay & Contactor Type	General Purpose Power Relay
------------------------	-----------------------------

Configuration Features

Coil Special Features	Coil Suppression Diode
Contact Number of Poles	1
Contact Arrangement	1 Form X SPST-NO-DM

Electrical Characteristics

Contact Switching Load (Min)	1A @ 12V
Coil Resistance	20 Ω
Contact Current Rating	120 A
Coil Voltage Rating	9 VDC, 16 VDC
Contact Voltage Rating	12 VDC
Coil Power Rating DC	8 W



Contact Features

Contact Material	Silver Alloy
------------------	--------------

Mechanical Attachment

Product Mounting Feature Type	Mounting Brackets
Product Mount Type	Chassis Mount

Dimensions

Product Width	76 mm[2.99 in]
Product Length	81 mm[3.18 in]
Product Height	50 mm[1.96 in]

Operation/Application

Current Type	DC
Coil Magnetic System	Monostable

Packaging Features

Packaging Method	Carton
------------------	--------

Other

Contact Current Class	120 A
-----------------------	-------