

# 1-102 Cams L35/45 Steel





## **Advantages**

- Cams with ramp and stop with 35mm and 45mm length for 1-point locking.
- 3-Point cam for 3-point locking.
- Rod control for 2-point locking.

### **Materials**

• Cams: steel, zinc plated

#### Remarks

1. ramp 3mm 2. stroke 18mm at 90° rotation 3. c-clips (are included) Cams L45 and 3-point cams with marking e) are supplied in 2 parts. Slide shoe for cams 35 and 45mm, see product system 1-103.



## Cams, L45

Part Number	H- dimension GI12	H- dimension GI18	H- dimension GI20	H- dimension GI22	H- dimension GI30	H- dimension GI32	H- dimension GI36	H- dimension GI40	H- dimension GI42	H- dimension GI46	H- dimension GI50	H- dimension GI56	H- dimension GI60	H- dimension GI66	Delivery Unit
200- a) 0408.00- 00000		8 mm	10 mm	12 mm	20 mm	22 mm	26 mm	30 mm	32 mm	36 mm	40 mm	46 mm	50 mm	56 mm	10 pcs.

## \* Accessories

1-103 Slide Shoe for Cams

1-260 Hooked Cam

1-261 Cams with Ramp

1-262 Cams variable

2-150 3-Point Cam L45, Rod Control

2-151 2-, 3- and 4-Point Cam Adapter

 $\hbox{2-15} \hbox{1.01 3-Point Adapter with H-Dimension Adjustment}\\$ 

2-151.04 3-Point Cam Adapter

