P/N FVS-367 REVISIONS CUSTOMER APPROVAL REVISIONS
A: ADDED 1/4-20 TAPPED HOLES / LMS 04-24-03
B: ADDED 1/4 NPT PORT / BB 10-10-2005
C: WAS 053X00221NM / MB 2-13-07
D: ADDED ASSEMBLY NOTES / MB 2-13-07
E: WAS ARC\_JO-032 / MB 10-30-07
F: REMOYED ASSEMBLY LY NOTES / MB 1-23-2012
G: WAS 1-1/2 UNF / LMS 1-30-19 DATE .27 DIA. MOUNTING HOLE - 4.85 F10546 (P6520-08-08) CAMOZZI 1/2 X 1/2 SWIVEL ELBOW-2 PLACES -2.25 -053X00331GM 24VDC 16VDC W/ SPECIAL SPRING RATE GROMMET HOUSING, 18" WIRE LEADS, #3 SEAT (3/32 ORIFICE) 12 10 2.50 123-GS-16VDC POWER VALVE WITH MANUAL OVERRIDE -1/2 NPT CLOSE NIPPLE .88 .66 1.75 .66 -MANUAL OVERRIDE SCREW DRIVER ADJUSTMENT 1/4 NPT PORT-\ ♦ ASP-4 1/2 NPT MUFFLER 1-14 UNS MALE THREAD <del>---</del> .75 → FLOW DIRECTION MANIFOLD BLOCK — 14CV 1/4 NPT CHECK VALVE ⑤ ⑥ ① 2.50 1/8 NPT PORT 1/4-20 X .63 DEEP TAPPED MOUNTING HOLES W/ FLUSH PLUG INSTALLED 2 PLACES TITLE: SPECIAL VALVE ASSEMBLY MATERIAL: FABCO-AIR PHONE: (352) 373-3578 FAX: (352) 375-8024 NOTED FVS-367-0L 10-18-01 E-MAIL: fabco@fabco-air.com | FOR: CFT / ARGUSS FIRE CONTROL