CLG-L239-800

AC lamps

 $> \ensuremath{\mathsf{CONTACT}}\xspace$ US

lumeis



CLG-L series LED lights are available with ON/OFF switch and different luminous flux. Available in AC version with the power cable included, this lamps offer the advantages of long service life and low consumption by LED technology.

Technical data				
APPROVALS				
Approvals	CE			
ELECTRICAL DATA				
Rated Voltage	230	V a.c.		
Rated Power	9	W		
Operating Voltage	207-253	V a.c.		
Frequency	50/60	Hz		
Appliance Class	II			
GENERIC DATA				
Casing Material	PC			
Electrical Connection	Connector			
Life Expectancy	20000	h at 25 °C		
	20000	h at 77 °F		
Cable Length	1800	mm		
	70.87	in		
Fixing System	Screws			
Switch	Manual ON/OFF			
PHOTOMETRIC DATA				
Color Temperature	6500	K		
Luminous Flux	823	Im		
ENVIRONMENTAL AND THERMAL DATA				
IP Protection Degree	IP20			

Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities clauses.



lumeis

CLG-L239-800

AC lamps

 $> \ensuremath{\mathsf{CONTACT}}\xspace$ US

Technical data		
Operating Temperature	-10÷50	°C
	14÷122	°F
Storage Temperature	-20÷60	°C
	-4÷140	°F

Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities clauses.



ENCLOSURE LAMPS "CLG-L" series LED lamps		lumeis
CLG-L239-800	AC lamps	> CONTACT US
Technical drawing mm (in)		
	425 (16.73)	

Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities clauses.

