

Saginaw Control and Engineering 95 Midland Road Saginaw, MI 48638-5770 (800) 234-6871 - Fax: (989) 799-4524 SCE@SaginawControl.com

Your Enclosure Source ®

SAGINAW



Construction

- Brushed Aluminum housing.
- Thermostat Range 0° to 100°F (-18° to 38°C).
- Heat discharge at the top of the heater.
- Panel mount.
- Air volume of 16 CFM on 125 & 200 Watt Heaters, 26 CFM on 400 & 800 Watt Heaters.
- Heat Indicator Light.
- Switch for Auto tuning on and off with the heating thermostat or set to Fan to run continuous & independent of the heating thermostat.
- Temperature differential hysteresis 5.4°F
- UL Recognized Component.

Application

Designed to protect electrical controls, instruments and sensitive components from low temperatures and the effects of condensation and corrosion by maintaining a stable temperature within the electrical enclosure. These heaters are not intended for use in hazardous, wet, dusty or dirty locations.

Finish

Brushed Aluminum

Industry Standards - (IS24)

UL Component Recognized

Notes

UL File #E358386 cULus Catigory NITW2 and NITW8

SCE-HF1251A

Product Specifications:

Part Number: SCE-HF1251A

Description: Heater W/Thermostat

Height: 5.41"
Width: 4.38"
Depth: 4.56"
Price Code: P1
List Price: \$424.42
Catalog Page: 402
Est. Ship Weight: 4.00 lbs
Model No.: KH 801

Volt: 120 VAC Watt: 125

Similar Part Numbers

SCE-HF1252AHeater W/ Thermostat (230 Volt)
SCE-HF13001CHeater W/ Thermostat
SCE-HF13002CHeater W/ Thermostat (230 Volt)
SCE-HF2001AHeater W/ Thermostat
SCE-HF2002AHeater W/ Thermostat (230 Volt)
SCE-HF4001BHeater W/ Thermostat
SCE-HF4002BHeater W/ Thermostat (230 Volt)
SCE-HF8001BHeater W/ Thermostat
SCE-HF8001BHeater W/ Thermostat

Installation Information

Fan/Heater with Thermostat