

Flexible Drive Couplings

Pump/Motor Mounts

Cylinder Rod End Alignment Couplers

> Fluid Power Accessories

<u>Hydrautic Manifolds &</u> <u>Manifolding Accessories</u>

Rydraulic Reservoirs



View Cart



Welcome to the: Magnaloy Products Store

This Store Front will allow you to enter your Magnaloy Product order directly to Magnaloy. Payment will be processed using your credit card information entered during the checkout process and a confirmation of the order and ship date will be emailed to you.

Please Note: our Shipping Cut-Off time is 2:00 PM Eastern Daylight Savings Time. Orders for in-stock items received before this time will be shipped the same day.

If you are ordering products and are TAX EXEMPT, please provide a Certificate of Tax Exemption to Magnaloy (fax: 989 354-4190). Otherwise, you may be charged a sales/use tax on your purchase.

Select the Product Line below:

Flexible Drive Couplings:

Magnaloy offers 9 models of magnesium drive couplings and 1 model of a powdered metal drive coupling. The PM90 model coupling (powdered metal) is available in bore sizes from 7/16 inch (12 mm) to 1 1/8 inch (28 mm) with torque ratings up to 672 in-lbs. The premium line of drive couplings (magnesium) are available in bore sizes from 3/8 inch (10 mm) up to 4 3/4 inch (120 mm) and torque ratings up to 71,763 in-lbs. Standard, metric and spline bores are available from stock and most other special & custom orders ship in 3 to 10 business days.



Pump/Motor Mounts:

Magnaloy offers the most complete line of pump/motor mounts in the industry. Mounts are available in aluminum casting or welded steel construction in horizontal and vertical designs for electric motor, gasoline or diesel engine to hydraulic pump applications. All mounts are machined to precision tolerances to assure proper alignment between the motor and pump pilot. Special configurations including metric sizes are our specialty.



Cylinder Rod End Alignment Couplers:

The Magnaloy Rod Alignment Coupler combines extended misalignment capabilities and strength to provide the most versatile alignment coupler available. The Magnaloy Rod Alignment Coupler is offered in two designs from 5/16-24 thread to 4 1/4-12 thread with a maximum rated load of 370,850 lbs. The M-Series provides 10° spherical misalignment and 1/8 inch lateral misalignment while the new R-Series provides 7 1/2° spherical misalignment and 1/8 inch lateral misalignment. The new R-Series design allows retro-fit from competitive brands while offering increased strength and misalignment capabilities. Both series are available in metric thread sizes.



Fluid Power Accessories

Magnaloy's accessory line includes a complete selection of Filler Breather Caps, Screens, Flanges and Adapters to allow custom design of filler breather




M - Series Dimensions



M - Series

	PART NO.	A THREAD SIZE	В	C	D	6	F	; 6	# *	1.46 1.4•	K	MAX RATED LOAD	PULL AT YEILD	APROX, WEIGHT (LBS.)
Ī	M010-01024 M010-01224	5/16-24 3/8-24	1.562	1.750	0.750	0.500	0.625	0.500	0.625	0.375	1.031	1,450 2,425	8,800 9,700	0.5
ĺ	M015-01420 M015-01620	7/16-20 1/2-20	1.562	2.000	0.750	0.750	0.625	0.500	0.625	0.500	1.031	3,250 4,450	13,000 17,800	0.6
	M020-02018 M020-02416 M020-02814	5/8-18 3/4-16 7/8-14	2.125	2.312	1.250	1.125	1.000	0.875	1,125	0.531	1.312	7,150 9,050 14,450	28,600 36,200 57,800	1.4
→	M030-10014	1-14	2.750	3.062	1.500	1.625	1.250	1.125	1.250	0.562	2.000	19,425	77,700	3.3
	M040-10812	1-1/4-12	3.500	4.000	2.000	2.000	1.500	1.250	1.687	0.750	2.500	30,825	123,300	6.9
	M050-1.1612 M050-12412	1-1/2-12 1-3/4-12	4.000	4.375	2.250	2.250	1.750 2.000	1.500	1.937	0.875	2.750	45,750 58,350	183,000 233,400	9.8
	M060-12812 M060-20012	1-7/8-12 2-12	5.000	5.625	3.000	3.000	2.250	2.000	2.625	1.375	3.375	67,550 77,450	270,200 309,800	19.8
	M070-20812	2-1/4-12	6.750	6.375	3.250	3.500	2.750	2.375	2.875	1.625	3.750	99,250	397,000	35.3
		2-1/2-12 2-3/4-12 3-12	7.000	6.500	4.000	3.500	3.250	2,875	3.375 3.375 3.500		3.875	123,750 150,950 180,850	603,800	45.3
	M100-30812	3-1/4-12	9.250	8.500	5.250	4.500	4.000	3.375	4.500	2.000	5.500	213,450	853,800	
	M140-40812	4 1/4-12	12.875	11.250	7.750	4.500	5.500	4.875	7.000	1.500	8.750	370,850	1,483,400	

^{*} Tolerance +/- .030 inch, all other dimensions +/- .015 inch



M - Series

magnaloy coupling company 501 Commerce Drive Alpena, MI 49707 989 356-2186

A Division of Douville Johnston Corporation Fax: 989 354-4190 http://www.magnaloy.com

183