


Cod. CR04000G3RL6



Technical characteristics: Body


- IP20 Protection degree
- Rated operational current Ie: 40A
- Rated thermal current Ith: 50A
- Rated insulation voltage Ui: 690V
- Rear Mounting
- Fixing with 2 screw at 28mm vertical
- Switching angle: 90°
- Class V2 self-extinguishing thermoplastic housing
- Assembled with metal shaft and threaded stud bolts to ensure maximum operating reliability
- Positive opening double break contacts, silver alloy made.



Technical characteristics: Plate and knob

- Yellow plate 67x67mm and red padlockable knob (max. 3 padlocks)
- IP66 Protection degree
- Fixing with 2 screw at 28mm vertical


Plate and positions



Electrical function

	0						
	1	X	X	X			
Contact		1	2	3	4	5	6
Element		1			2		


Electrical scheme



Cod. CR04000G3RL6


Dimensions

measures in mm (in)



Drilling templates

measures in mm (in)



Cod. CR04000G3RL6

			CR040	
Technical data IEC 947-3 EN 60947-3				
Rated insulation voltage	Ui	V	690	
Rated operating voltage	Ue	V	690	
Rated impulse withstand voltage	Uimp	kV	6	
Rated thermal current for open switch	Ith	A	50	
Rated thermal current for enclosed switch	Ithe	A	50	
Rated operation frequency		Hz	50/60	
Power dissipation for each pole		W	1,3	
Rated operating current				
AC-21A Switching resistive loads, including moderate overloads	Ie	A	40	
AC-22A Switching of mixed resistive and inductive loads, including moderate overloads	Ie	A	32	
AC-20A Connecting and disconnecting under no loads conditions			-	
Rated operating power				
AC-23A Switching of motor loads or other highly inductive loads 3 phase - 3 pole	230V	Kw (A)	10 (32)	
	400V	Kw (A)	18,5 (30)	
	500V	Kw (A)	18,5 (27)	
	690V	Kw (A)	18,5 (19)	
AC-23A Switching of motor loads or other highly inductive loads 1 phase - 2 pole	110V	Kw (A)	3 (34)	
	230V	Kw (A)	5,5 (30)	
AC-3 Squirrel cage motors: starting, switching off motors during running 3 phase - 3 pole	230V	Kw (A)	7,5 (24)	
	400V	Kw (A)	15 (27)	
	500V	Kw (A)	15 (22)	
AC-3 Squirrel cage motors: starting, switching off motors during running 1 phase - 2 pole	690V	Kw (A)	16 (16)	
	110V	Kw (A)	2,2 (25)	
	230V	Kw (A)	4,5 (25)	
AC-4 Squirrel cage motors: starting, pluggign, inching	400V	Kw (A)	-	
	230V	Kw (A)	3 (10)	
AC-15 Control of a.c electromagnetic loads	400V	Kw (A)	5,5 (10)	
	230V	A	10	
Rated breaking capability in AC-23A (cos φ=0,45)	400V	A	8	
	230V	A	256	
	400V	A	240	
Short circuit protection				
Rated short time withstand current	Icw	A	500	
Rated short-circuit make capacity	Icm	A	2000	
Rated conditional short-circuit current	-	kA	10	
With fuses class gG	500V	A	50	
Technical data UL/CSA				
Rated operating voltage	Ue	UL/CSA V	600/600	
General use current	Ie	UL/CSA A	40/32	
Short circuit rating @600Vac		Arms	5000	
Fuse size (Class RK5, 600Vac, 200kA A.I.C.)		A	60	
Rated operating power				
1 phase - 2 pole	120V	Hp (A)	3 (34)/2,5	
	240V	Hp (A)	7,5 (40)/4,5	
3 phase - 3 pole	200V	Hp (A)	10 (32,2)/-	
	240V	Hp (A)	15 (42)/9,5	
	480V	Hp (A)	20 (27)/20	
	600V	Hp (A)	20 (22)/25	
Mechanical characteristics				
Mechanical life		Cycles x 10 ⁶	1,5	
		Cycles/hour	120	
Connection according to IEC 9471-1 and EN 50947-1				
Connecting capability	With flexible wires	Min-Max	mm2	2x2,5-10
		Min-Max	AWG	14-8
	With solid wires	Min-Max	mm2	2x2,5-16
Connection terminal screw dimensions		Type		M4
Screw tightening torque		Nm		1,7
Protection degree IEC 529 EN 60529				
Terminals		IP		20
Ambient conditions				
Operating ambient temperature		°C		-25 ÷ +55
Storage ambient temprature		°C		-30 ÷ +70
Withstand to constant humid according to IEC 60068				2-78
Withstand to cyclic humid according to IEC 60068				2-30

Standard

IEC/EN 60947-3; UL508

Approvals

