



IMTEX VALVE POSITION MONITOR - MODEL SELECTOR

SRA-D-IIC-VPM

Imtex Type SRA Valve Position Monitor incorporating 2 x switches / sensors. IP.66/67 rated anodised aluminium (powder coated) enclosure with bolt-on cover, (2) conduit entries and green / red high visibility position indicator. Certified Ex d flameproof.

	1	2	3	4	5		6	
Model #	TYPE	FUNCTION	ENCLOSURE	CONDUIT	OUTPUT DRIVE	INDICATOR	FEATURE SUFFIX	IDENT
	SRA	16	9	5	M	R	-	I OO ° RC

Technical Specification

SRA	Valve Position Monitor, GP / Ex d
16	SPDT Mechanical Switch (up to 2)
9	Aluminium (Anodised & Coated)
5	(2) M20 x 1.5
M	25mm Namur Drive Shaft
R	Red (Closed) / Green (Open)
-	
I	Ex d
OO °	V3 SPDT Mechanical Switch (Silver Plated Contacts)
RC	TR CU Certification

Application Note

Not Applicable

SRA-D-IIC-VPM

Certification

TR CU (EAC) 1Ex db IIC T4/T6 Gb X / Ex tb IIIC Db X

Ambient Temperature Range

-50 Deg.C to 85 Deg.C (T4)

Minimum to Maximum of Product Type

(NB Please refer to electrical function used for specific recommended limits)

Dimensional Drawing No.

SRA-DIM010 (Namur)

Electrical Parameters

10A @ 125/250VAC / 0.5A @ 125VDC

